



270 North Road, Yate  
South Gloucester BS37 7LQ  
[www.action-products.co.uk](http://www.action-products.co.uk)

## PRODUCT INFORMATION



Tel: 01454-228702  
Fax: 01454-228703  
[sales@action-products.co.uk](mailto:sales@action-products.co.uk)

DESIGNED TO BE KIND

Professional Chemical Products

### SAFE GRAFFITI REMOVER (GEL)

NON-METHYLENE CHLORIDE NON-CAUSTIC NON-ACIDIC

EP Patent No. 0925335 US Patent No.6632782

#### METHOD – Graffiti Removal from hard surfaces:

##### Method: -

Wear impervious rubber gloves to remove softened paint. Wear goggles. Maintain good ventilation.

1. Use **Safe Graffiti Remover** as a cleaning gel. Apply generously, with a brush. Use the brush to lay the product on, do not brush out. For small areas, apply on a soft cloth. Time needed depends on the graffiti to be removed:

To remove	Dwell time needed	Method
Felt pen	None	Wipe on/wipe off
Paint pen	Approx 30 seconds	Wipe on, wait , wipe off
Spray paint	As needed. 5 minutes to an hour	Wipe on, wait , wipe off
Gloss paint	As needed. 10 minutes to an hour	Brush on, wait , wipe off

2. When the gel has soaked into the graffiti and it is fully softened, wipe off with a soft cloth. Always leave products to soak fully into and soften the coating to be removed. This means that a minimal amount of mechanical work is required hence the underlying surface will not be damaged by enthusiastic hacking or scraping.

3. Rinse well with water. Ensure that no trace of chemicals remain. Allow to dry.

N.B. **Safe Graffiti Remover** does not contain toxic or harmful ingredients, but if the paint contained lead, the waste will have to be disposed of accordingly.

**Caution.** Test before use on plastics. Wear protective goggles when working overhead or outdoors if breezy conditions. Wear butyl rubber gloves to remove softened coating. Prolonged contact with **Graffiti Remover** or **Wash** will soften paint, polystyrene, some grades of Perspex and Polycarbonate. **Safe Graffiti Remover** and **Graffiti Wash** are quite safe and may, by themselves, be disposed of via public drainage systems, but the advisability of this depends upon the type and nature of graffiti that has been removed.



Made in England



**BFiY Winner 2002**