



270 North Road, Yate
South Gloucester BS37 7LQ
www.action-products.co.uk

PRODUCT INFORMATION



Tel: 01454-228702
Fax: 01454-228703
sales@action-products.co.uk

DESIGNED TO BE KIND

Professional Chemical Products

SAFE GRAFFITI REMOVER (GEL)

Use with

GRAFFITI WASH

NON-METHYLENE CHLORIDE NON-CAUSTIC NON-ACIDIC

EP Patent No. 0925335 US Patent No.6632782

METHOD – Graffiti Removal from brick & masonry:

Method: -

Wear impervious rubber gloves to remove softened paint. Wear goggles. Maintain good ventilation.

1. Apply **Safe Graffiti Remover** generously, with a brush. Use the brush to lay the product on, do not brush out.

2. Allow 30 minutes dwell time. This is ample time to remove most paints. Test a small area. If not fully softened, leave for extra time, testing at 10 minute intervals. Always leave products to soak fully into and soften the coating to be removed. This means that a minimal amount of mechanical work is required hence the underlying surface will not be damaged by enthusiastic hacking or scraping.

3. Scrub away the softened paint. **Safe Graffiti Remover** does not contain toxic or harmful ingredients, but if the paint contained lead, the waste will have to be disposed of accordingly.

4. Use **Graffiti Wash** as supplied. Do not dilute. Spray **Graffiti Wash** onto treated surface. Scrub firmly enough to generate a foam and cause deep cleaning of the surface, but ensure that bristles are not so stiff as to cause surface damage.

5. When surface cleaning has been achieved, rinse thoroughly with clean cold water. Ensure that no traces of chemicals remain. Allow to dry.

Caution. Prolonged contact with **Safe Graffiti Remover** or **Graffiti Wash** will soften paint, polystyrene, some grades of Perspex and Polycarbonate. **Safe Graffiti Remover** and **Graffiti Wash** are quite safe and may, by themselves, be disposed of via public drainage systems, but the advisability of this depends upon the type and nature of paint surfaces which have been removed.



Made in England



BFiY Winner 2002