



PRODUCT INFORMATION



270 North Road, Yate
South Gloucester BS37 7LQ
www.action-products.co.uk

Tel: 01454-228702
Fax: 01454-228703
actionproducts@onetel.com

DESIGNED TO BE KIND

Household - DIY - Professional Chemical Products

SAFE PAINT & VARNISH REMOVER (GEL)

NON-METHYLENE CHLORIDE NON-CAUSTIC

EP Patent No. 0925335

ABOUT THE PRODUCT

VERSATILITY **Safe Paint & Varnish Remover**, new formula - removes various varnishes and paints including, gloss, emulsion, vinyl silk, flecked, textured chlorinated rubber paints and Hammerite™. A truly all-purpose paint remover.

SPEED + EFFICIENCY Faster than other safe strippers. Many other safe strippers need to be left overnight. **Safe Paint & Varnish Remover** can remove up to 2-3 coats of some gloss paints in approx 40 minutes, can remove up to 4 coats of vinyl silk in 30 minutes and textured paint in 50-60 minutes. (Times may vary in individual cases. Some gloss paints will need an hour or two.)

Easy to use - suitable for DIY and professional users.



ECONOMY Labour saving. Recyclable plastic packaging – reduced disposal costs.

- SAFETY**
- * Non corrosive
 - * Non harmful to handle.
 - * No obnoxious vapours.
 - * No dangerous vapours.
 - * No damage to rubber gloves.
 - * No damage to plastic or vinyl
 - * No damage to substrate

USER FRIENDLINESS

Safe to use. No objectionable odours. Pleasant to use - not harmful or painful if in contact with skin.



Made in the United Kingdom



BFiY Winner 2002



ENVIRONMENTAL FRIENDLINESS

Based on biodegradable, neutral, non-toxic, non corrosive ingredients.

WHERE TO USE

Safe Paint & Varnish Remover is a thick gel with excellent non-drip characteristics. Use on exterior wood, metal, stone, bricks and mortar. Use on interior wood, metal, plaster, stone, floor tiles, ceramic tiles, glass.

WHAT IT DOES

Safe Paint & Varnish Remover soaks into and softens gloss, emulsion, vinyl silk, interior textured, Hammerite™, chlorinated rubber paints, modern water based and old spirit based varnishes. This allows easy removal from the substrate.

COVERAGE

- 1 litre covers from 2-4 square metres.
- 5 litres covers from 10-20 square meters.
- 25 litres covers up to 100 square metres.

HOW TO GET THE BEST RESULTS

1. Stir well before use.
2. Protect all areas not to be stripped.
3. Pour product into any suitable container.
4. Apply a generous coat by brush. **DO NOT BRUSH OUT.** Wait about 30-40 minutes. (40-50 minutes for textured paint.) **DO NOT ALLOW TO DRY OUT.** (If product dries out, spray with warm water to reactivate.)
5. Check a small area with a scraper to ensure that Safe Remover has fully penetrated into the paint. If not, wait and check again. Remove softened paint.
6. If any paint remains - repeat the above process.
7. Wash area with water. Ensure no trace of remover remains. Allow to dry before redecorating.
8. Wash hands after use.

Caution: Protect eyes when working overhead.
 Wear impervious gloves to remove softened paint.
 Prolonged contact will dissolve polystyrene and damage Perspex.
 Prolonged contact will dissolve nail polish and acrylic false nails.

Whilst Action Products Limited has taken every care to ensure accuracy of the data contained in this document; no guarantee or liability will be assumed. It is recommended that customers satisfy themselves of the suitability of all product purchased for their own use.

STORAGE

Keep container securely closed. Store out of direct sunlight. Protect from frost.

DISPOSAL OF WASTE

Collect waste for disposal. If paint removed contained lead, then the waste material will contain lead. Relevant regulations will apply.

™ Hammerite is a trademark of ICI Paints Ltd.